



## "Y" Strainer

**PN 16 / PN 25 / PN 40 / 150# / 300#**

TEST PRESSURE, kg / sq. cm.

TESTING	HYDRAULIC			
	PN 16	PN 40	150#	300#
BODY	24	60	31	78

@ PN 40 #

SIZE	PORT	L	H	H1	ØWh	ØD	b	Øg	f	ØJ	N	K:PCD
50	51	230	278	298	200	165	20	102	3	18	4	125
65	64	290	306	328	250	185	22	122	3	18	8	145
80	76	310	328	353	250	200	24	138	3	18	8	160
100	102	350	390	422	350	235	24	162	3	22	8	190
150	152	480	450	495	400	300	28	218	3	26	8	250
200	203	600	543	602	480	375	34	285	3	30	12	320
250	254	730	651	724	480	450	38	345	3	33	12	385
300	305	850	772	857	600	515	42	410	3	33	16	450
350	337	980	-	-	-	580	54	465	4	36	16	510
400	387	1100	-	-	-	660	60	535	4	39	16	585
450	438	1200	-	-	-	685	66	560	4	39	20	610
500	489	1250	-	-	-	755	72	615	4	42	20	670
600	590	1450	-	-	-	890	84	735	5	48	20	795

- Size : ½" (15 mm) to 2" (50 mm) - Threaded End  
 2" (50 mm) to 24" (600 mm) - Flanged End
- Class : 150# / 300# / 600# / 900# / PN6 / PN25 / PN40
- End : Flanged / Threaded / Socket Weld Ends
- Design : Mfg. Standard
- Features : Strainer Screens - Perforeted + Wire mesh
- \*Special Material & Higher Size also available on request.